

## MBRFSX6636


65.5" x 35.75" x 22.5"

**Installation:** Freestanding

# 323/4! $4 \frac{1}{2}$ flat surface for 65% mounting faucets 12' 26" 231/4" 353/4"

Features a 4.5"-wide flat deck surface on the drain side for mounting faucetry.

The drain and overflow assembly is concealed between the walls of the tub, eliminating the need for an exposed drain kit.



#### **GENERAL SPECIFICATIONS:**

Material Acrylic

120 lbs / 54.43 kg Soaker Weight

Maximum Fill 78 gal

NOTE: Filling this tub to the maximum may require an above average size or

dedicated water heater.



inside view of tub



Virtual Spout integrated high-flow tub filler. See 'packages and options' below.

### **PACKAGES AND OPTIONS**

Hydrotherapy Package	Package Contents	Part #
Soaker	soaking bath - no jets; textured bottom, pre-leveled foam base	MBSRFSX6636
Soaker with Virtual Spout	soaking bath - no jets; includes Virtual Spout integrated high-flow tub filler (see important information below), textured bottom, pre-leveled foam base	MBSRFSX6636VS

#### **OPTIONS**

Standard Color - White

Color Upgrade - Biscuit (MBFSCOL)

Quick Ship - reduces lead time - call for availability

Lift & Turn Drain Kit -

Chrome (MBWOC); Brushed Nickel (MBWOBN), White (MBWOW)

NOTE: Tub includes an access panel (standard), for drain or Virtual Spout installation. Depending on how the tub is positioned, the panel may be visible. Access panel can be elminated by request, which will increase installation difficulty. Must specify on order.

#### IMPORTANT INFORMATION

- · Options listed cannot be combined with Designer Collection options.
- Specifications and configurations are subject to change without notice.
- Measurements are  $\pm 1/2$ " and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.
- The Virtual Spout is installed below the water level of the tub. MTI supplies a Wilkins dual check valve and an Acme inwall atmospheric vent to prevent backflow into the potable water supply. However, some areas of the country require additional backflow prevention when water is introduced to the bath below the water level (check local codes).

